

Quantum Flex™ Markers

P.O. Box 2848 • Anaheim, 92804 • 714-563-9749 • 714-776-6208 -FAX



Quantum Test-O-Flex™ Cathodic Protection Test Station

A two terminal cathodic protection test station that doubles as a cost effective, durable, flexible pipeline marker. Manufactured from a continuous glass fiber reinforced polyester composite, this non conductive, above ground test station has been designed to provide trouble free monitoring of electrical currents & potentials on underground pipelines & other metallic structures. Flexible, composite construction greatly reduces the likelihood of knocked down or damaged test stations due to vandalism or equipment exposure. Dual purpose design eliminates the added cost of placing a test station & a pipeline marker at your test location. Sleek, low profile terminal access does not draw unwanted attention to the marker. To the untrained eye the Test-O-Flex looks like a standard pipeline marker, thus reducing sabotage and / or vandalism.

Features

Weather Resistant

Quantum Test Stations are constructed from a fiberglass reinforced composite which is ultraviolet resistant and temperature stable. They will not become brittle when cold or soften under heat, thereby remaining flexible in virtually all weather conditions.

Lower Maintenance

Solid color impregnated throughout the test station. Never needs painting! Will not fade and crack like thermoplastic or conduct electricity like metal test stations. The Test-O-Flex is securely anchored with a factory supplied soil anchor, thereby reducing the likelihood of pull out.

Flexible

Capable of withstanding substantial field abuse. Returns upright after vehicle & livestock impacts, thus greatly reducing the added cost of maintenance associated with marker repair or replacement.

Easy Access

The test points are easily accessible for fast readings. No cumbersome caps or covers to remove that are often lost or stolen.

Versatile

Designed to accommodate a warning message on both sides of the marker, thereby serving as a dual purpose test station and pipeline marker all in one. Can also be used as a tracer wire access point for conductive locating of non-metallic pipelines.

Lightweight

Strong composite material is 75% lighter than steel & 10 times stronger than typical thermoplastic. Easily stores and transports to the job site.

Fire Resistant

Capable of withstanding small grass fires and controlled ditch burns. Will not soften and melt like common plastic.



TEST-O-FLEX™


SPECIFICATIONS

QM - TOF

Material: Glass Reinforced Polyester Composite
 Weight: 0.55 lbs per foot
 *Standard Length: 66 inch
 Width: 3 15/16 inch
 *Standard Color: Yellow

* Custom colors or lengths available upon request

TEST POINTS



Test points consist of 4" copper tubes that are crimped with a standard wire tool for fast and convenient installation.


OPTIONS

Test-O-Flex™ Includes: marker post, standard 1 color generic warning decal, anchor assembly, copper contact points and cathodic protection ID decal. Prewired test station is optional.

The test station can be prewired to your specifications. Custom decals are also available upon request.



Contact Points are located in a 1" notch, 2" from the top of the test station. Dual sided, recessed web surface offers decal protection in the event of vehicle impacts.



SOIL ANCHOR

Test-O-Flex is supplied with a pull out resistant soil anchor. The composite soil anchor is riveted to the test station at the factory.